



Mercedes-Benz

service information

TO: ALL MERCEDES-BENZ PASSENGER CAR DEALERS

DATE: January 1997

REF. NO. MBNA 72/14

**SUBJECT: MODELS 124, 129, 140 and 202
REPLACEMENT OF DOOR INTERIOR TRIM PANEL COMPONENTS**

On the above models, door interior trim panel components, such as arm rests and door pockets (where available as spare parts) can be replaced using the retaining clips listed below, with the exception of model 202 rear doors (see SI MBNA 72/13, May 1995, for model 202 rear door interior panel disassembly/assembly procedure).

Interior door trim panel component replacement procedure

1. Remove the interior trim panel assembly (See SMS, group 72 for work instructions on removing/installing trim panels).
2. Using cutting pliers or a 5/8 inch chisel and hammer, remove the rounded portion of the plastic mounting studs (back side of trim panel) of the component being replaced.

WARNING!

Always wear eye protection when removing the rounded portion of the plastic mounting studs. Use extra caution so that only the rounded portion is removed and the surrounding area of the door interior trim panel is not damaged.

3. Insert the new component into the door interior panel, and while providing support to the component, press the clips onto the studs securely.
4. Trim the studs to 1 mm above the clip.
5. Reinstall trim panel.

Parts Information

Qty.	Part Name	Part Number
As needed	Clip	000 994 06 48

Order No. S-SI-MBNA-72/14

This bulletin has been created and maintained in accordance with MBNA-SLP 5.1, Document and Data Control, and MBNA-SLP 16.1, Control of Quality Records.

© 1996 Mercedes-Benz of North America, Inc.
Mercedes-Benz Canada, Inc.
Technical Information

All rights reserved. Reproduction or translation in whole or in part is not permitted without authorization from the publisher. Printed in U.S.A.